



- 规格说明: Specifications:
 电气特性: Electrical:
 1. 额定电流: Current Rating
 1.5A/contact terminal
 2. 额定电压: Voltage Rating
 30V DC
 3. 接触阻抗: Contact Resistance
 30 milliohms MAX
 4. 耐电压: Dielectric Withstanding Voltage:
 500 V AC AT Sea Level
 5. 绝缘阻抗: Insulation Resistance:
 1000MΩ/ohms MIN
- 物理性能: Mechanical:
 1. 插拔力: Connector Mate and Umate Force
 Mate force: 3.75kgf(MAX)
 Umate force: 1.02kgf(MIN)
 2. 端子保持力: Terminal Retention
 1.2kgf(MIN)
- 原材料: Material:
 1. 塑胶: Housing: High Temperature Thermoplastics, UL 94V-0 PBT White
 2. 端子: Contact: Copper Alloy C2680
 3. 外壳: Shell: Copper Alloy C2680/SPCC
- 电镀: Finish:
 1. 端子: Contact: Plated gold in Mating Area; Tin on Solder Tails
 2. 外壳: Shell: Nickel Plating

NOT SCALED
DRAWING

TOLERANCE UNLESS
OTHERWISE NOTICE

INCH

MM

DR.
Nina

DATE

HENGLIAN ELECTRONIC TECHNOLOGY CO., LTD

HL-USB

THIRD ANGLE PROJECTION

LINEAR
MM
INCH

.00±0.01
.000±0.005
.0000±0.002

.00±0.25
.000±0.13
.0000±0.05

CKD
Jack

MAY-06-12

DWG. NO.

HL012052181

MM
INCH

ANGLE+0° 30'

RADIL

+0.45
-0.15

APPD
Jack

MAY-06-12

恒连电子科技有限公司
<http://www.chinarj45.com>