



1. 塑壳: 641D 10P4C, ABS, 象牙色;
2. 接触电镀: Fu"
3. 电子线: UL 1061 26#
4. 电子线长: 4 × 300mm, 半剥头2mm;
5. 线序:
PIN2-白色
PIN3-橙色
PIN4-黑色
PIN7-绿色
其余空位

- NOTES:
- MATERIAL:
- | | |
|---------------------|--|
| 1. HOUSING MATERIAL | :ABS(UL 94V-0); Ivory; |
| 2. CONTACT MATERIAL | :ROUND PINS-0.46mm DIAMETER
PHOSPHOR BRONZE;
GOLD PLATING OVER NICKEL; Fu" |
| 3. WIRES | :UL 1061 26 AWG |
- ELECTRICAL/PHYSICAL:
- | | |
|---------------------------------------|---------------------------|
| 1. VOLTAGE RATING | :125 VAC RMS |
| 2. CURRENT RATING | :1.5 AMP |
| 3. CONTACT RESISTANCE | :30 MILLIOHMS MAX2 |
| 4. INSULATION RESISTANCE | :500 MEGOHMS MIN @500V DC |
| 5. DIELECTRIC WITHSTANDING RESISTANCE | :1000V AC RMS 60Hz. 1MIN |
| 6. DURABILITY | :750 CYCLES MIN |
| 7. TEMPERATURE | :-40°C/+85°C |

除非另行说明, 否则公差按照下表		设计	RD	比例	1: 1
尺寸标注	公差	审核		单位	mm
.X	±0.25 ±2.0°	批准		图幅	A4
.X	±0.20 ±1.5°	角法		版本	A-0
.XX	±0.15 ±1.0°			图数	第1页 共1页
.XXX	±0.10 ±0.5°				

H 恒连电子科技有限公司

641D 10P4C 象牙色 L=300mm (UL1061-26#) 半剥

http://www.chinarj45.com

产品型号: 641D 10P4C 象牙色 L=300mm (UL1061-26#) 半剥

产品编号: _____ 图纸编号: _____